

## CAT.6 UTP MINI SHUTTERED KEYSTONE JACKS - CN6UTBK/S



Browse on Mobile

 [Browse on Web](#)

NEXCONEC® Category 6 unshielded tool free RJ-45 keystone jacks exceed the transmission line performance requirements of IEC and TIA for CLASS-E/Category 6 systems. Their compact design has been engineered to optimize density in high performance applications such as Data Centers. Each Cat 6 unshielded RJ-45 keystone jacks comply with **IEC 60603-7-4** (Unshielded) and support all applications designed for CLASS-E networks, as defined within **ISO/IEC 11801** (2nd Edition): 2010 including ATM 1200, 1000BASE-T (Gigabit Ethernet) and 1G FCBASE-T.

With its shuttered design which offers the dust free and well protection to the contact pins inside Keystone jack.

### FEATURES

- ✓ Easy and fast tool free termination
- ✓ Fits all keystone style face plates and floor boxes
- ✓ Suitable for modular unscreened patch panel installation



### APPLICATIONS

- ✓ Support Class E/category 6 standards networks
- ✓ Terminates 23AWG to 26AWG cables

## SPECIFICATIONS

Parameters	Value
Plastic Material	High quality engineering plastic
Jack Wire	Stamp Pin 0.35mm, Phosphor Bronze Gold over Nickel Plating
IDC Conductor	0.5mm Phosphor Bronze, Tin-plating
Jack Contact Life	Min. 750 Insertions
Contact Compatibility	Accommodate 23 to 26 AWG Solid
Wiring Block Life	Min. 200 term. cycles
PCB	FR-4, 1.2mm Thickness
Termination	180° Termination
Termination Wiring	TIA-568A or TIA-568B
TIA Cat.6 Perm. Link Test	Worst Pair NEXT Headroom $\geq 3.0\text{dB}$
Operating Temperature	-10°C / +60°C
Operating Humidity	10% ~ 90% RH
Storage Temperature	-40°C ~ +68°C
Compliance	ANSI/TIA-568.2-D-2018, ISO/IEC 11801-1-2017, YDT926.3-2009, ISO/IEC 60603-7-4
RoHS	RoHS Directive 2011/65/EU
Warranty	12 Months
Packing	25pcs per carton

## ORDER INFORMATION

Product	Part Number	Product Description
	<b>CN6UTBK/S</b>	NEXCONEC Keystone Jack Cat.6 Unshielded, Black, with Shutter
	<b>CN6UTWH/S</b>	NEXCONEC Keystone Jack Cat.6 Unshielded, White, with Shutter

TECHNICAL DRAWING

