

INLINE ENCLOSURE - OC-DO03A



Browse on Mobile

 Browse on Web

OC-DO03A is designed to seal without screws. The compact size and flip-over cover bring easy operation as well as complete function. The splice trays are jointed with a hinge at one side, which makes the operation in each tray easier. It is designed to prevent from operation damage.

FEATURES

- ✓ Total 4 trays with maximum capacity of 96 cores.
- ✓ 16 SC adapter and micro splitter can be installed.
- ✓ This connector box is suitable for wall mounting and pipeline.
- ✓ The hinge is used for the fiber trays, which is convenient for the operation of each fiber trays.
- ✓ No screw page-turning structure plug and play, fast response for new subscribers.
- ✓ Production grade: IP68

SPECIFICATIONS

Parameters	Value
Style	In-line/ Horizontal
Dimensions (LxWxH)	380 x 245 x 130 mm
Weight (Kg)	3.0 - 4.0 Kg
Material	PP+GF
Cable Ports	1 uncut port (Φ10~17.5 mm); 2 branch ports (Φ10~17.5 mm) 16 drop cable ports (2*3 mm soft cable or Φ3~8 mm round cable)
Fiber Splice Capacity	144
Tray Capacity	24F/96F
Tray Count	4
Application	Wall /Pole Mounting
Sealing Structure	Mechanical Seal
Sealing Rating	IP68
Operating Temperature	-40°C ~ +65°C
Impact Strength	16 N.m / IK09





SPLICE TRAY SPECIFICATIONS

Type	38#
Tray Capacity	4 x 24F/96F
Dimensions	112 x 68 x 8 mm
Splitter	None
Single Core	Yes
Ribbon Core	No

STANDARD ACCESSORIES (Pictures for reference only)

Item	Picture	Description	Qty	Status
1		Allen Spanner	1 pc	Packed
2		Insulation tap	1 roll	Packed
3		Protection sleeves 12pcs/bag	On demand	Packed
4		Nylon cable tie	1 bag	Packed
5		Choke plug	2 pcs	Packed
6		Installation manual	1 set	Packed
7		φ4mm Winding pipe	1 roll	Packed
8		EVA tube	1 roll	Packed
9		Sealing kits	1 set	Packed
10		φ16-25mm hose clamp	4 pcs	Packed
11		Tighten tool	1 set	Packed
12		Desiccant	1 pc	Packed
13		Clean paper	1 pc	Packed
14		Silicon oil	1 pc	Packed

OPTIONAL ACCESSORIES (Pictures for reference only)

Item	Picture	Description	Qty	Status
1		Air Valve	1 set	Packed
2		Ground lead	1 set	Packed
3		Pole mounting fittings	1 set	Packed
4		Wall mounting fittings	1 set	Packed

ORDER INFORMATION

Part Number	Product Description
OC-DO03A	Fiber Optic Inline Enclosure up to 96 Splices Incl. 16 Ports SC SX Adapter Ports

TECHNICAL DRAWING

