

POWER CORDS C13-C14







NEXCONEC® power extension cords are a reliable solution to power connectivity problems. These IEC320-C14 to IEC-320-C13 cables are designed for small data center, office workstation and other lower-amp applications. This C14 male to C13 female cord can be used to power a computer, server or monitor, attach a server or drive to a UPS system or PDU or extend an existing connection up to 10-ft. (3.05 m).

FEATURES

- Available in LSZH and PVC jacket material
- Oxygen-free copper conductor
- **RoHS & CE compliant**
- Wire gauge 18AWG
- Available in different colors and lengths

APPLICATIONS

- Connect devices like computers, servers and monitors to a PDU
- Provide a high-quality replacement for a worn-out or missing power cord
- Rated at 250V 10A Maximum



SPECIFICATIONS

| Connector A | C13 IEC-320 |
|-----------------------|---------------------------------------|
| Connector B | C14 IEC-320 |
| Maximum Input Amps | 10A |
| Voltage Compatibility | 100-250V |
| Gauge | 18 AWG |
| Conductor Material | Oxygen-free Copper |
| Number of Conductors | 3 Wires (Black, White, Green) |
| Jacket Outer Diameter | 6.8 ± 0.2mm |
| Jacket Material | PVC |
| Jacket color | Available in Black, Red, Blue , Green |
| Standard | IEC60320 , CE and RoHS Compliant |

ORDER INFORMATION

| PN Black | PN Blue | PN Red | PN Green | Product Description | Length |
|----------|---------|---------|----------|---|--------|
| PWR0.6K | PWR0.6B | PWR0.6R | PWR0.6G | Power Cable C13-C14 18AWG 10A 250V IEC320 CE , 0.6m (2ft) | 0.6m |
| PWR0.9K | PWR0.9B | PWR0.9R | PWR0.9G | Power Cable C13-C14 18AWG 10A 250V IEC320 CE , 0.9m (3ft) | 0.9m |
| PWR1.2K | PWR1.2B | PWR1.2R | PWR1.2G | Power Cable C13-C14 18AWG 10A 250V IEC320 CE , 1.2m (4ft) | 1.2m |
| PWR1.5K | PWR1.5B | PWR1.5R | PWR1.5G | Power Cable C13-C14 18AWG 10A 250V IEC320 CE , 1.5m (5ft) | 1.5m |
| PWR1.8K | PWR1.8B | PWR1.8R | PWR1.8G | Power Cable C13-C14 18AWG 10A 250V IEC320 CE , 1.8m (6ft) | 1.8m |

TECHNICAL DRAWINGS

